

Safety Zone

6 Mil Anti-Graffiti Film

MECHANICAL PROPERTIES

Thickness	6 mil multi-ply
Tensile Strength at Break	28,000 PSI
Break Strength	125 lb/inch
Elongation at Break	150%
Peel Strength	5 lb/inch



OPTICAL & SOLAR PROPERTIES

Visible Light Transmitted	85 %
Visible Light Reflected	11 %
Ultra Violet Block	93 %
Total Solar Energy Reflected	10 %
Total Solar Energy Transmitted	75 %
Total Solar Energy Absorbed	15 %
Shading Coefficient	0.92
Total Solar Energy Rejected	19 %

Safety Zone

6 Mil Anti-Graffiti Film

MECHANICAL PROPERTIES

Thickness	6 mil multi-ply
Tensile Strength at Break	28,000 PSI
Break Strength	125 lb/inch
Elongation at Break	150%
Peel Strength	5 lb/inch



OPTICAL & SOLAR PROPERTIES

Visible Light Transmitted	85 %
Visible Light Reflected	11 %
Ultra Violet Block	93 %
Total Solar Energy Reflected	10 %
Total Solar Energy Transmitted	75 %
Total Solar Energy Absorbed	15 %
Shading Coefficient	0.92
Total Solar Energy Rejected	19 %



Hanita Coatings



Hanita Coatings